# A. P. Nonweiler Co., Inc.

# SAFETY DATA SHEET

www.apnonweiler.com

# SECTION 1: CHEMICAL AND MANUFACTURER IDENTIFICATION

Product Name: Luxe NanoShield Product Code: 5000R942

A.P. Nonweiler Co., Inc. 24 Hour Emergency: INFOTRAC: 1-800-535-5053

3321 County Road A PO Box 1007

Oshkosh, WI 54903-1007

(920) 231-0850

E-mail: sds@apnonweiler.com

Outside U.S. and Canada: Infotrac: 352-323-3500

INFOTRAC Customer ID: 72826

NOTE: INFOTRAC and National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire,

exposure or accident involving chemicals

#### Not recommended for:

Because many of the conditions are within the user's knowledge and control, it is essential that the user evaluate and determine whether the product is suitable and appropriate for a particular use and intended application, and complies with all local applicable laws, regulations, standards, and guidance.

# SECTION 2: HAZARD(S) IDENTIFICATION

Prepared according to Global Harmonized System (GHS) Standards

GHS Classification Scale 1=Severe Hazard; 4=Slight Hazard

### **GHS Ratings:**

Flammable liquid 3 Flash point >= 23°C and <= 60°C (140°F)

Aspiration hazard 1 Aspiration Toxicity Category 1: Known (regarded)- human

evidence - hydrocarbons with kinematic viscosity? 20.5 mm2/s at

40° C.

#### **GHS Hazards**

H226 Flammable liquid and vapour

H304 May be fatal if swallowed and enters airways

#### **GHS Precautions**

P210	Keep away from heat, sparks, open flames and hot surfaces. No smoking!
P233	Keep container tightly closed

P240 Ground / bond container and receiving equipment

P241 Use explosion-proof electrical, ventilating, lighting equipment

P242 Use only non-sparking tools

P243 Take precautionary measures against static discharge

P280 Wear protective gloves, protective clothing, eye protection, face protection

P331 Do NOT induce vomiting

SDS for: 5000R942 Page 1 of 7

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

P303+P361+P353 IF ON SKIN (or hair): Remove / Take off all contaminated clothing immediately. Rinse

skin thoroughly with water / shower

P370+P378 In case of fire: Use dry chemical / CO2 / foam for extinction

P405 Store locked up

P403+P235 Store in a well ventilated area. Keep cool

P501 Dispose of contents / container to an approved waste disposal facility

### Signal Word: Danger





# SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS number	Weight Concentration %
tert-Butyl acetate	540-88-5	50.00% - 60.00%
Polyurethane Hybrid		30.00% - 40.00%
Solvent naphtha, petroleum, light aromatic	64742-95-6	5.00% - 10.00%

# SECTION 4: FIRST AID MEASURES

Inhalation: Move affected person to fresh air. If breathing has stopped, administer CPR. If the person vomits, clean the airway and turn their head to the side to prevent choking. If the person is unconscious but breathing, place them stably on their left side in the recovery position. Never give anything by mouth to an unconscious person. Seek immediate medical attention.

**Eyes:** Flush eyes gently with clean water for at least 15 minutes. If irritation persists, seek immediate medical attention.

**Skin:** Remove any contaminated clothing using appropriate gloves. Rinse skin thoroughly for 15 minutes in a shower or with a hose. Seek immediate medical attention.

<u>Ingestion:</u> Rinse mouth with water to remove any residual chemical. If the person vomits, clean their airway and turn their head to the side to prevent choking. DO NOT induce vomiting and DO NOT give them anything to drink unless directed to do so by a physician. If the person is unconscious but breathing, place them stably on their left side in recovery position. Never give anything by mouth to an unconscious person. Seek immediate medical attention.

Additional Notes to Physician - Treat symptomatically. No specific antidote available

### SECTION 5: FIREFIGHTING MEASURES

Flash Point: 35 C (95 F)

LEL: N/A UEL: N/A

# **Suitable Extinguishing Media:**

Foam

Carbon Dioxide (CO2)

**Dry Chemical** 

Specific Hazards During Firefighting: Prevent firefighting run-off from entering drains or sewers.

SDS for: 5000R942 Page 2 of 7

<u>Byproducts of Combustion:</u> Fires involving this product may release oxides of carbon and nitrogen, reactive hydrocarbons, and irritating vapors.

<u>Unusual Fire and Explosion Hazards:</u> Any closed container may rupture when exposed to extreme heat. Use a water spray to cool sealed containers. Solvent vapors are heavier than air and can travel along the ground.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### Spill / Leak Clean-Up Procedures:

Immediately turn off or isolate any source of ignition (pilot lights, electrical equipment, flames, heaters, etc.). Evacuate area and ventilate. Personnel wearing proper protective equipment should contain spill immediately with inert materials (sand, earth, chemical spill pads of cotton) by forming dikes. Dikes should be placed to contain spill in a manner that will prevent material from entering sewers and waterways. Large spills, once contained, may be picked up using explosion proof, non-sparking vacuum pumps, shovels, or buckets, and disposed of in suitable containers. If a large spill occurs notify the appropriate authorities.

In case of road spill or accident contact INFOTRAC (1-800-535-5053).

CAUTION: If spilled material is cleaned up using a regulated solvent, the resulting waste mixture will also be regulated.

Do not empty into drains. All disposal must comply with federal, state, and local regulations. The material, if spilled or discarded, may be a regulated waste. Refer to state and local regulations. Department of Transportation (DOT) regulations may apply for transporting this material when spilled. See Section 14.

### SECTION 7: HANDLING AND STORAGE

# **Handling Precautions:**

Open containers carefully and in a well ventilated area, and use appropriate respiratory protection. Wash hands thoroughly after handling. Keep containers closed when not in use. Do not transfer to unmarked containers. Empty containers contain product residue which may exhibit hazardous properties therefore, do not pressurize, cut, glaze, weld or use for any other purpose. Return drums to reclamation center for proper cleaning and reuse.

#### **Storage Requirements:**

Store in a cool, dry, well ventilated area. Keep containers tightly closed and store away from heat, sparks, open flame or oxidizing materials. Extended storage at excessive temperatures may produce odorous and toxic fumes from product decomposition.

### SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
tert-Butyl acetate 540-88-5	200 ppm TWA; 950 mg/m3 TWA	200 ppm TWA	NIOSH: 200 ppm TWA; 950 mg/m3 TWA
Polyurethane Hybrid	Not Established	Not Established	Not Established

SDS for: 5000R942 Page 3 of 7

Solvent naphtha, petroleum,	Not Established	Not Established	Not Established
light aromatic 64742-95-6			

<u>Engineering Controls:</u> Avoid creating dust or mist. Local exhaust ventilation, process enclosures, or other engineering controls are required when handling or using this product to avoid over exposure. Use explosion-proof ventilation equipment. Do not use in closed or confined spaces. Keep all levels below exposure limits. Perform regular monitoring to ensure exposure limits are not exceeded.

#### Personal Protective Equipment (PPE):

**Respiratory Protection** - Do not breathe vapors. When concentrations exceed the established limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA) until vapors are exhausted. Observe OSHA standard 29 CFR 1910.134 and ANSI Z88.2 requirements whenever workplace conditions require a respirators use.

**Hand Protection** - Wear appropriate protective gloves and clothing to prevent skin exposure. Gloves must be inspected prior to use. Use proper glove removal technique (without touching gloves outer surface) to avoid skin contact with this product.

**Eye Protection** - Use safety eyewear with splash guards or side shields. Use additional eye protection such as chemical safety goggles when the possibility for eye contact from splashing, spraying liquid, or airborne material exists.

**Skin Protection** - Avoid contact with this product. Wear appropriate protective gloves and clothing to prevent skin exposure. Use proper glove and clothing removal techniques to avoid skin contact with this product. When handling large quantities, eye wash stations and deluge showers should be available.

#### **Hygiene Measures:**

**General** - When using do not eat or drink. Wash hands with soap and water before breaks and at the end of each workday.

Contaminated Equipment - Avoid contact with contaminated clothing and protective gear/equipment. Wash before reuse.

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

This mixture typically exhibits the following properties under normal circumstances:

Appearance Liquid Dispersion	Odor Organic Solvent
Physical State Liquid	Specific Gravity (SG) 0.9800
Lbs VOC/Gallon Less Water 2.39	Flash point: 35°C, 95°F
g VOC/L Less Water 286.68	Boiling range: N/A

# SECTION 10: STABILITY AND REACTIVITY

#### **Product Stability (under normal conditions):**

**STABLE** 

Incompatible Materials: Strong acids, strong bases, oxidizing agents

SDS for: 5000R942 Page 4 of 7

Hazardous Decomposition Products: Carbon Dioxide (CO2), Carbon Monoxide (CO), Oxides of Nitrogen (NOx), dense black smoke

Hazardous polymerization will not occur.

#### **SECTION 11:** TOXICOLOGICAL INFORMATION

#### **Mixture Toxicity**

Note - Toxicological studies have not been performed on this mixture. The toxicological data listed is compiled using data from the components of the mixture. Refer to Section 2 of this SDS for GHS classification of acute and chronic effects of exposure.

#### **Principle Routes of Exposure:**

Skin Contact Inhalation Eve Contact Ingestion

May cause damage to the following organs:

Eyes Central Nervous System Respiratory System

Carcinogenicity: The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing) or ACGIH (optional listing):

**CAS Number Description** % Weight Carcinogen Rating Solvent naphtha, petroleum, 5% - 10% EU REACH: Present (P) 64742-95-6

light aromatic

#### **ECOLOGICAL INFORMATION SECTION 12:**

Bioaccumulative Potential: No data available

Mobility in Soil: No data available

Persistence and Degradability: No data available

**Component Ecotoxicity** 

tert-Butyl acetate 96 Hr LC50 Pimephales promelas: 296 - 362 mg/L [flow-through]

Solvent naphtha, petroleum, light 96 Hr LC50 Oncorhynchus mykiss: 9.22 mg/L aromatic 48 Hr EC50 Daphnia magna: 6.14 mg/L

#### **SECTION 13:** DISPOSAL CONSIDERATIONS

Do not discharge product into sewer system. Dispose of in a licensed facility. Waste management should be in full compliance with federal, state, and local laws.

The transportation, storage, treatment and disposal of RCRA waste material must be conducted in compliance with 40 CFR 262, 263, 264, 268 and 270. Chemical additions, processing, or otherwise altering this material may make the waste management information presented in this SDS incomplete, inaccurate or otherwise inappropriate.

#### TRANSPORT INFORMATION **SECTION 14:**

This material is classified for transport as follows:

**Proper Shipping Name UN Number** Packing Group Hazard Class Agency

U.S. DOT Paint 1263 Ш 3

#### REGULATORY INFORMATION **SECTION 15:**

Additional regulatory listings where applicable

SDS for: 5000R942 Page 5 of 7 State of California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986) WARNING! This product contains the following substance(s) which are listed by the State of California as carcinogenic, or a reproductive toxin:

- None

Clean Air Act, Section 112, Hazardous Air Pollutants (HAPs) (see 40 CFR 61) This product contains the following substance(s) which are listed as hazardous air pollutants (HAPs) per the Clean Air Act:

- None

Massachusetts Right To Know This product contains the following toxic or hazardous substance(s) which appear on the Massachusetts Substance List:

540-88-5 tert-Butyl acetate

New Jersey Worker and Community Right to Know Hazardous Substance List The following substance(s) appear on the New Jersey Right to Know Hazardous Substance List:

540-88-5 tert-Butyl acetate

Commonwealth of Pennsylvania Worker and Community Right To Know Act This product contains the following substance(s) which appear on the Pennsylvania Hazardous Substance List:

540-88-5 tert-Butyl acetate

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) This product contains a chemical or chemicals which are subject to the reporting requirements of the Act, and Title 40, of the Code of Federal Regulations, part 372:

- None

Canadian DSL All substances in this product except those listed below are listed or exempt from reporting:

540-88-5 tert-Butyl acetate

64742-95-6 Solvent naphtha, petroleum, light aromatic

<u>Country</u>	<u>Regulation</u>	All Components Listed
Canada	Canadian NDSL	No
Australian	Australian Inventory of Chemical Substances	No
Japan	Existing and New Chemical Substances	No
China	Inventory of Existing Chemical Substances Produced	No
New Zealand	Inventory of Chemicals	No
Philippines	Philippine Inventory of Chemicals and Chemical	No
	Reach PBT/vPvB	No

TSCA Substance Control Act (TSCA) All substances except those listed below appear in the Toxic Substances Control Act, Chemical Substance Inventory:

None

#### **SECTION 16:** OTHER INFORMATION

Disclaimer: The Volatile Organic Compound (VOC) content reported herein, if any, is based on a material VOC calculation. Several methods are used for the calculation of VOC content, and the standards and requirements regarding VOC content vary by location or jurisdiction.

This document has been prepared using data from sources considered to be technically reliable and is believed to be correct as of the date hereof. It does not constitute a warranty, expressed or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond the seller's control. User is responsible

SDS for: 5000R942 Page 6 of 7

Printed: 2/29/2024 at 5:01:35PM

to evaluate all available information when using product for any particular use, and to comply with all federal, state, provincial, and local laws and regulations.

### **Revision Notes:**

Reviewer Revision

Date Prepared: 2/29/2024

SDS for: 5000R942